








Micro OX

Cod.

Generatori di ossigeno modelli Micro OX.

Cod.	Press. ingresso	Press. scarico	Purezza ox. 93%	Conness. Entrata	Conness. Uscita
MICRO OX-3.5 TA-GO-007	7	8	3.4	1/2"	1/2"
MICRO OX-4.5 TA-GO-008	7	5	4.3	1/2"	1/2"
MICRO OX-6 TA-GO-009	7	5	6	1/2"	1/2"
MICRO OX-9 TA-GO-010	7	5	8.6	1/2"	1/2"
MICRO OX-12 TA-GO-011	7	5	12	1/2"	1/2"
MICRO OX-18 TA-GO-012	7	5	17	1/2"	1/2"
MICRO OX-24 TA-GO-013	7	5	24	1/2"	1/2"
MICRO OX-36 TA-GO-015	7	5	36	1/2"	1/2"
MICRO OX-48 TA-GO-016	7	5	48	1/2"	1/2"

Cod.	 Potenza	 Volt. Hz	 Ciclo	 Dimensioni	 Peso netto
MICRO OX-3.5 TA-GO-007	-	230V 50Hz	100 %	mm 700x700x1700	Kg 450
MICRO OX-4.5 TA-GO-008	kW 0.3	230V 50Hz	100 %	mm 1230x1120x2200	Kg 500
MICRO OX-6 TA-GO-009	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 760

Cod.	Potenza	Volt. Hz	Ciclo	Dimensioni	Peso netto
MICRO OX-9 TA-GO-010	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 850
MICRO OX-12 TA-GO-011	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 1120
MICRO OX-18 TA-GO-012	-	230V 50Hz	100 %	mm 1600x1200x2100	Kg 1730
MICRO OX-24 TA-GO-013	-	230V 50Hz	100 %	mm 1850x1200x2200	Kg 2350
MICRO OX-36 TA-GO-015	-	230V 50Hz	100 %	mm 1600x1800x2100	Kg 3450
MICRO OX-48 TA-GO-016	-	230V 50Hz	100 %	mm 1850x2050x2200	Kg 4700

* Con temperatura aria compressa in ingresso nel generatore = 30°C